

Tacryl PRO is a two component pure acrylic resin for orthotic and prosthetic sockets.

| TYPICAL PROPERTIES | Appearance | Clear liquid |
|---|---|-------------------------|
| | Туре | Cross-linkable |
| | Color Hazen(APHA)(ASTM D-1209) | <50 |
| | Solid (%)(ASTM D-1259) | 30±1 |
| | Refractive index n _D ²⁰ (ASTM D-1218) | 1.44±0.01 |
| | Viscosity at 25°C(cP)(ASTM D-562) | 800-1300 |
| | Density at 25°C(g/ml)(ASTM D-1475) | 1.01 |
| | | |
| RECOMMENDATIONS FOR END-USE | Orthotic and prosthetic sockets | |
| FORMULATING GUIDELINES | See our guide formulation for spe | cific information |
| | See our gaine formulation for spe | |
| STORAGE Store container tightly closed in | | ry area for a maximum 6 |
| | months. Avoid temperatures exce | eding 30°C. |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

The information contained herein is correct and reliable to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee, as conditions and methods of use of our products are beyond our control. We suggest that you evaluate these recommendations in your own laboratory prior to use.

TECHNICAL DATA SHEET



