Taak Resin

TYPICAL PROPERTIES	Appearance	Appearance Clear liquid		
	 Type 	Thermoplastic acrylic	stic acrylic resins solution	
	 Solvent 	Toluene		
	 Solubility 	Soluble in:		
		 Aromatic hydro 		
			phatic hydrocarbons	
		 Esters & Ketone 	2S	
		Insoluble in:		
		 Alcohols Come of the physical 		
		 Some of the gly 	COIS	
	e Color Ha	700(ADHA)/4STMD 1200)	<50	
		zen(APHA)(ASTM D-1209) rdner(ASTM D-1544)	<1	
			<1 60±1	
	• Solids(%)(AST		<5	
		g KOH/g)(<i>ASTM D-1639</i>)		
	• Tg(°C)		+37	
		5°C (cP)(ASTM D-562)	10000-20000	
		°C(g/ml)(ASTM D-1475)	0.96	
	 Flash point(°C 	C) (ASTM D-93)	22	
FILM PROPERTIES	Hard, tough,	flexible and clear		
	 Very good ad 	hesion on alkaline surface	es(asphalt, concret	
	etc.)			
	 Fast drying 			
	 Very good ab 	rasion resistance		
		Very good weather resistance		
	, .	Very low dirt pick -up		
RECOMMENDATIONS FOR END-	JSE Marking pain	ts, Traffic marking paints		
		Protective coatings on concrete and asbestos cement.		
	See our guide	See our guide formulation for specific information.		
STORAGE	Should be sto	ored indoors in sealed cor	tainers for a	

The information contained herein is correct and reliable to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee, as conditions and methods of use of our products are beyond our control. We suggest that you evaluate these recommendations in your own laboratory prior to use.



TECHNICAL DATA SHEET

